



# Krytox™

## Performance Lubricants

# H-1 Food Grade Lubricants

## Oils and Greases for the Food Processing Industry

Choosing the right lubricant for your equipment just got a lot easier with H-1 certified Krytox™ food grade oils and greases from Chemours.

As with the full line of Krytox™ lubricants, Krytox™ oils and greases deliver superior performance with advanced features of high-temperature stability, nonflammability, and chemical and biological inertness. Krytox™ lubricants will not carbonize or form gummy deposits that typically cause failures, nor will they evaporate. Therefore, maintenance costs can be significantly reduced.

The composition of Krytox™ lubricants allows them to function in a wide range of operating temperatures and chemical environments. Krytox™ lubricants will not break down under mechanical stress. The oils are clear, colorless, and odorless, and the grease is white.

Krytox™ lubricants comply fully with USDA performance standards for designated uses. These lubricant products are not intended to be used as direct food additives. Use Krytox™ oils and greases whenever a long-lasting, tenacious, chemically inert lubricant is needed for your demanding applications.



ISO 9001:2008 certified



## Stability and Compatibility

Krytox™ oils contain only carbon, oxygen, and fluorine. The oils will not burn or support combustion, even in 100% liquid or gaseous oxygen. They are chemically inert and will not break down in the presence of most chemicals.

Because Krytox™ lubricants are essentially inert, they are safe to use with most metals, plastics, and seal materials, and they are completely resistant to water and steam.

Krytox™ lubricants protect bearings and other components under a wide range of load and speed conditions. Components run quieter, and wear protection is extended. Krytox™ lubricants will not break down under extreme pressure or high mechanical stress.

Various grades of Krytox™ lubricants are serviceable for long periods of time at continuous temperatures between -60–300 °C (-58–600 °F). There are also special grades that can routinely handle temperatures of 350 °C (662 °F) and withstand peaks up to 400 °C (752 °F) for shorter periods of time.

Use Krytox™ lubricants on chains, bearings, valves, seals, or any place a long-lasting lubricant is needed.

## Safety and Environmental Protection

Using Krytox™ greases and oils:

- Reduces the need for hydrocarbon lubricants
- Helps allay any concerns about emissions or other potential environmental impact
- Avoids the inconvenience and cost associated with the disposal of hydrocarbon-based oils and greases.

Krytox™ greases and oils are non-toxic, easy to handle, and do not release volatile organic compounds to the atmosphere. Additionally, Chemours has a regeneration program that reclaims used oil and restores it to its original properties. This lowers the overall cost of lubrication, and eliminates safety and environmental disposal problems.



In an oven at 232 °C (448 °F) for 40 hr, Krytox™ lubricant had 0% weight loss.



Hydrocarbon-based lubricants burn; Krytox™ lubricants do not.

## Benefits in Use

The extended life you will see with Krytox™ lubricants means longer re-lubrication intervals, less maintenance, and improved cleanliness. The overall superior stability of Krytox™ lubricants also can result in less downtime and fewer failures due to lubricant carbonization, evaporation, or other deterioration. Water washout and steam cleaning will not affect Krytox™ lubricants. In addition, because Krytox™ lubricants can be used in many applications and last so long, your total lubricant inventory can be reduced, as well as the need for frequent movement of drums around your facility.

The combination of all of these factors translates to long-term cost savings for your business.



In an oven at 232 °C (448 °F) for 40 hr, the hydrocarbon lubricant had 40% weight loss.

**Applications for Krytox™ H-1 Food Grade Lubricants**

Type	Products	Applications	Comments
Multipurpose Greases	Krytox™ GPL 202 Krytox™ GPL 203 Krytox™ GPL 205 Krytox™ GPL 206	Bearings, valves, seals, O-rings	For non-corrosive environments at standard operating temperatures
Anti-Corrosion Greases	Krytox™ GPL 223 Krytox™ GPL 225 Krytox™ GPL 226 Krytox™ FG 34	Bearings, valves, seals, O-rings	For corrosive environments at standard operating temperatures
High-Temperature Greases	Krytox™ XHT-SX Krytox™ XHT-AC Krytox™ XHT-ACX	Bearings and chains	Krytox™ XHT-AC and ACX contain corrosion inhibitor
Lubricating Oils	Krytox™ GPL 105 Krytox™ XHT-500 Krytox™ XP-1A5 Krytox™ FG 40	Chains, compressors, bearings, gear boxes	Krytox™ XHT-500 is formulated for high temperatures; Krytox™ XP-1A5 contains corrosion inhibitor
Vacuum Pump Fluids	Krytox™ 1506 Krytox™ 1514 Krytox™ 1525	Mechanical pumps	

**Additional Information and Literature Requests**

More detailed data sheets showing specific properties for each Krytox™ lubricant product are available upon request.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

---

For product information, industry applications, technical assistance, or global distributor contacts, visit [krytox.com](http://krytox.com) or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.

© 2015 The Chemours Company FC, LLC. Krytox<sup>™</sup> and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours<sup>™</sup> and the Chemours Logo are trademarks of The Chemours Company.

Replaces: H-96058-4  
C-10391 (11/15)